

Fine Ribbed (Corrugated) surface one side - fine cloth impression reverse side


Description: High quality electrical safety matting fully tested to 20,000 volts with regulation standard stamped on reverse of roll at 1000mm intervals.

Dialectric test voltage: 20,000 volts,

Surface proof tested: 10,000v

maximum safety working voltage of 7,500v.

It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.



- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance
- THIS GRADE DOES NOT CONTAIN RECYCLED RUBBER

Cut lengths available to order. 552 can also be supplied to order in colours and flame retardant, low smoke emission grades

Stock Roll Sizes [m x m x mm]	Weight [kg/M2]	Specifications [compound]	Values [typical]
10m x 0.91m x 4.5mm	5.20	Colour:	Black
22.86m x 0.91m x 4.5mm	5.20	Compound:	NR
10m x 1.2m x 4.5mm	5.20	Hardness [shore A]:	65°
22.86m x 1.2m x 4.5mm	5.20	Density[SG]:	1.25
		Tensile Strength:	5 MPA
		Elongation[min]:	300%
		Abrasion Resistance:	180 mm ³
		Minimum Temperature	-20°C
		Maximum Temperature	+70°C

Technical Information	
Application	Electrical Safety, General Purpose, Health & Safety
Product	7.5 Kv Working Voltage, Anti Slip, ASTM D178 ANSI JS.7 Type 1 Class 1, Electrical Safety, Safety Matting
Thickness	4.5mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.

Fine Ribbed (Corrugated) surface one side - fine cloth impression reverse side


Description: High quality electrical safety matting fully tested to 20,000 volts with regulation standard stamped on reverse of roll at 1000mm intervals.

Dialectric test voltage: 30,000 volts,

Surface proof tested: 20,000v

maximum safety working voltage of 17,500v.

It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.



- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance
- THIS GRADE DOES NOT CONTAIN RECYCLED RUBBER

Cut lengths available to order. 553 can also be supplied to order in colours and flame retardant, low smoke emission grades

Stock Roll Sizes [m x m x mm]	Weight [kg/M2]	Specifications [compound]	Values [typical]
10m x 0.91m x 6.5mm	8.45	Colour:	Black
22.86m x 0.91m x 6.5mm	8.45	Compound:	NR
10m x 1.2m x 6.5mm	8.45	Hardness [shore A]:	65°
22.86m x 1.2m x 6.5mm	8.45	Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperature	-20°C
		Maximum Temperature	+70°C


Technical Information

Application	Electrical Safety, General Purpose, Health & Safety
Product	17.0 Kv Working Voltage, Anti Slip, ASTM D178 JS.7 Type 1 Class 2, Electrical Safety, Safety Matting
Thickness	6.5mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.

Fine Ribbed (Corrugated) surface one side - fine cloth impression reverse side

Description: High quality electrical safety matting fully tested to 30,000 volts with the regulation standard, stamped on the reverse of the roll at 1000mm intervals. Dielectric test voltage: 40,000 volts,
Surface proof tested: 20,000v
maximum safety working voltage of 26,000v.
It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.



- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance
- THIS GRADE DOES NOT CONTAIN RECYCLED RUBBER

Cut lengths available to order. 554 can also be supplied to order in colours and flame retardant, low smoke emission grades


Stock Roll Sizes [m x m x mm]	Weight [kg/M2]	Specifications [compound]	Values [typical]
10m x 0.91m x 9.5mm	8.45	Colour:	Black
		Compound:	NR
		Hardness [shore A]:	65°
		Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperature	-20°C
		Maximum Temperature	+70°C

Technical Information	
Application	Electrical Safety, General Purpose, Health & Safety
Product	26.0 Kv Working Voltage, Anti Slip, ASTM D178 JS.7 Type 1 Class 3, Electrical Safety, Safety Matting
Thickness	9.5mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.

Fine Ribbed (Corrugated) surface one side - fine cloth impression reverse side

Description: High quality electrical safety matting fully tested to 30,000 volts with the regulation standard, stamped on the reverse of the roll at 1000mm intervals. Dielectric test voltage: 50,000 volts,
Surface proof tested: 40,000v
maximum safety working voltage of 36,000v.
It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.



- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance
- THIS GRADE DOES NOT CONTAIN RECYCLED RUBBER

Cut lengths available to order. 555 can also be supplied to order in colours and flame retardant, low smoke emission grades

Stock Roll Sizes [m x m x mm]	Weight [kg/M2]	Specifications [compound]	Values [typical]
10m x 0.91m x 12.7mm	16.51	Colour:	Black
		Compound:	NR
		Hardness [shore A]:	65°
		Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperature	-20°C
		Maximum Temperature	+70°C

Technical Information

Application	Electrical Safety, General Purpose, Health & Safety
Product	36.0 Kv Working Voltage, Anti Slip, ASTM D178 JS.7 Type 1 Class 4, Electrical Safety, Safety Matting
Thickness	12.7mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.